

Submittal Sheet

Jet-Rite Series

Water Systems Tank

Job Name: _____ Schedule #: _____

Location: _____ Model #: _____

Engineer: _____ Representative: _____

Contractor: _____

Materials of Construction

Shell: Drawn steel w/ polyurethane paint finish

Diaphragm: Butyl rubber w/ copolymer polypropylene liner

Connection: Stainless steel nipple
(PJR 6-PJR25S-3/4" nipple)
(PJR 44-PJR66S- 1" nipple)

Description

Jet-Rite (PJR) tanks are a diaphragm type, pre-charged hydro-pneumatic tank designed for residential and commercial water well, pressure booster, and irrigation systems.

Ratings

Max. Working Pressure: 125 PSI

Max. Working Temp: 140 F

Pre-Charge (adjustable): 28 PSI



Tank Specifications

Model	Diameter (inches)	Height (inches)	System Connection (inches)	Volume (gallons)	Drawdown (gallons)			Weight (lbs)
					20/40	30/50	40/60	
PJR 6	8.0	12.0	3/4	2.1	.8	.7	.6	5.0
PJR 15	11.0	14.5	3/4	4.8	1.7	1.5	1.3	10.0
PJR 20S	11.4	13.5	3/4	5.3	1.9	1.6	1.4	13.3
PJR25	12.5	18.9	3/4	9.0	3.1	2.6	2.3	15.4
PJR 25S	12.5	18.9	3/4	9.0	3.1	2.6	2.3	15.4
PJR 44IL	16.3	19.75	1	14.0	5.1	4.3	3.8	23.3
PJR 44S	16.3	20.8	1	14.0	5.1	4.3	3.8	27.0
PJR 66S	16.3	28.5	1	20.0	7.6	6.5	5.5	38.0

